



## Baykee VP Series Line Interactive UPS 1000VA

<b>Model #</b>	<b>VP-1000</b>
Capacity	1000VA/600W
Front panel & Rear panel	
Rear panel	
Transformer size	105*45mm (Aluminum)
AVR	3 steps of AVR, CPU controlled
<b>INPUT</b>	
Input voltage range	145~290Vac±5Vac
Input frequency range	50Hz / 60Hz (Auto sensing)
<b>OUTPUT</b>	
Output voltage range	200~255Vac
Output frequency (DC mode)	50±0.5Hz / 60±0.5Hz
Wave form	PWM (DC Mode)
Transfer time	Typical 2~6ms, Max.10ms.
<b>BATTERY</b>	
QTY & capacity of battery	2 pc*12V7Ah
Charging period	4~6 hours recover to 90% capacity
<b>PROTECTION &amp; FUNCTION</b>	
PROTECTION	<ol style="list-style-type: none"> <li>1. Battery low voltage protection</li> <li>2. Overload protection</li> <li>3. Short circuit protection</li> <li>4. Surge Protection</li> </ol>
FUNCTION	<ol style="list-style-type: none"> <li>1. Auto re-starts when AC recovers</li> <li>2. Silence setup</li> <li>3. Automatic charging (offline charging)</li> </ol>
<b>MANAGEMENT</b>	
RJ45/11 & USB	Optional
<b>PHYSICAL</b>	
Unit dimension (mm)	345*146*162
Gross weight (1pc, kg)	11.2
Net weight (1pc, kg)	11.0
*Product specifications are subject to change without further notice.	